



## 300 4x2

ENGINE DISPLACEMENT (CC)	270
ENGINE TYPE	SOHC, 4-stroke
BORE & STROKE (MM)	72.7x65.2
COOLING SYSTEM	Liquid with fan
TRANSMISSION	Automatic CVT
DRIVE SYSTEM	2 WD
OVERALL WIDTH (IN./CM)	41.4/105.16
OVERALL HEIGHT (IN./CM)	44/111.8
OVERALL LENGTH (IN./CM)	73.6/186.9
WHEELBASE (IN./CM)	46.4/117.9
SUSPENSION TRAVEL FRONT (IN./CM)	5/12.6
SUSPENSION TRAVEL REAR (IN./CM)	5/12.6
GROUND CLEARANCE (IN./CM)	10.2/25.9
SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Swing Arm

FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	22x7-10 (4)
TIRE REAR (PRESSURE)	22x10-10 (3.5)
FUEL CAPACITY (GAL./LITERS)	3.3/12.5
RACK CAPACITY - FRONT (LBS./KG)	50/22.7
RACK/BOX STORAGE CAPACITY - REAR (LBS./KG)	100/45.4
TOWING CAPACITY (LBS./KG)	500/226.8
ALTERNATOR CAPACITY (AMPS)	12.5
SPEEDOMETER	Digital
ODOMETER	Digital
DRY WEIGHT (LBS./KG)	477/216.4
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Red

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



## 300 DVX

ENGINE DISPLACEMENT (CC)	270
ENGINE TYPE	SOHC, 4-stroke
BORE & STROKE (MM)	72.7x65.2
COOLING SYSTEM	Liquid with fan
TRANSMISSION	Automatic CVT
DRIVE SYSTEM	2 WD
OVERALL WIDTH (IN./CM)	44.7/113.5
OVERALL HEIGHT (IN./CM)	44.7/113.5
OVERALL LENGTH (IN./CM)	67.7/172
WHEELBASE (IN./CM)	46.4/117.9
SUSPENSION TRAVEL FRONT (IN./CM)	6.1/15.5
SUSPENSION TRAVEL REAR (IN./CM)	6.5/16.5
GROUND CLEARANCE (IN./CM)	10.5/26.7

SUSPENSION TYPE - FRONT	Double A-Arm
SUSPENSION TYPE - REAR	Swing Arm
FRONT BRAKES	Hydraulic Disc
REAR SERVICE BRAKE	Hydraulic Disc
TIRE FRONT (PRESSURE)	21x7-10 (4)
TIRE REAR (PRESSURE)	20x11-9 (3.5)
FUEL CAPACITY (GAL./LITERS)	3.3/12.5
ALTERNATOR CAPACITY (AMPS)	12.5
DRY WEIGHT (LBS./KG)	425/192.8
MINIMUM OPERATOR AGE	16
AVAILABLE COLORS	Black/White

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE