



650 H1

| | |
|----------------------------------|-------------------------|
| ENGINE DISPLACEMENT (CC) | 641 |
| ENGINE TYPE | SOHC, 4-stroke, 4-valve |
| BORE & STROKE (MM) | 98x85 |
| COOLING SYSTEM | Liquid with fan |
| TRANSMISSION | Automatic CVT with EBS |
| DRIVE SYSTEM | 2/4 WD + Diff Lock |
| OVERALL WIDTH (IN./CM) | 47.5/120.6 |
| OVERALL HEIGHT (IN./CM) | 48/121.9 |
| OVERALL LENGTH (IN./CM) | 84.8/215.4 |
| WHEELBASE (IN./CM) | 50/127 |
| SUSPENSION TRAVEL FRONT (IN./CM) | 10/25.4 |
| SUSPENSION TRAVEL REAR (IN./CM) | 10/25.4 |
| GROUND CLEARANCE (IN./CM) | 11/27.9 |
| SUSPENSION TYPE - FRONT | Double A-Arm |
| SUSPENSION TYPE - REAR | Double A-Arm |

| | |
|--|----------------|
| FRONT BRAKES | Hydraulic Disc |
| REAR SERVICE BRAKE | Hydraulic Disc |
| TIRE FRONT (PRESSURE) | 25x8-12 (5) |
| TIRE REAR (PRESSURE) | 25x10-12 (5) |
| FUEL CAPACITY (GAL./LITERS) | 5.7/21.6 |
| RACK CAPACITY - FRONT (LBS./KG) | 100/45.4 |
| RACK/BOX STORAGE CAPACITY - REAR (LBS./KG) | 200/90.8 |
| TOWING CAPACITY (LBS./KG) | 1050/476.3 |
| ALTERNATOR CAPACITY (AMPS) | 25.0 |
| SPEEDOMETER | Digital |
| ODOMETER | Digital |
| DRY WEIGHT (LBS./KG) | 692/313.9 |
| MINIMUM OPERATOR AGE | 16 |
| AVAILABLE COLORS | Black |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



550 H1 EFI

| | |
|----------------------------------|-------------------------|
| ENGINE DISPLACEMENT (CC) | 545 |
| ENGINE TYPE | SOHC, 4-stroke, 4-valve |
| BORE & STROKE (MM) | 92x82 |
| COOLING SYSTEM | Liquid with fan |
| TRANSMISSION | Automatic CVT with EBS |
| DRIVE SYSTEM | 2/4 WD + Diff Lock |
| OVERALL WIDTH (IN./CM) | 47.5/120.6 |
| OVERALL HEIGHT (IN./CM) | 48/121.9 |
| OVERALL LENGTH (IN./CM) | 84.8/215.4 |
| WHEELBASE (IN./CM) | 50/127 |
| SUSPENSION TRAVEL FRONT (IN./CM) | 10/25.4 |
| SUSPENSION TRAVEL REAR (IN./CM) | 10/25.4 |
| GROUND CLEARANCE (IN./CM) | 11/27.9 |
| SUSPENSION TYPE - FRONT | Double A-Arm |
| SUSPENSION TYPE - REAR | Double A-Arm |

| | |
|--|----------------|
| FRONT BRAKES | Hydraulic Disc |
| REAR SERVICE BRAKE | Hydraulic Disc |
| TIRE FRONT (PRESSURE) | 25x8-12 (5) |
| TIRE REAR (PRESSURE) | 25x10-12 (5) |
| FUEL CAPACITY (GAL./LITERS) | 5.7/21.6 |
| RACK CAPACITY - FRONT (LBS./KG) | 100/45.4 |
| RACK/BOX STORAGE CAPACITY - REAR (LBS./KG) | 200/90.8 |
| TOWING CAPACITY (LBS./KG) | 1050/476.3 |
| ALTERNATOR CAPACITY (AMPS) | 25.0 |
| SPEEDOMETER | Digital |
| ODOMETER | Digital |
| DRY WEIGHT (LBS./KG) | 692/313.9 |
| MINIMUM OPERATOR AGE | 16 |
| AVAILABLE COLORS | Green or Camo |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



550 H1 EFI LE

| | |
|----------------------------------|-------------------------|
| ENGINE DISPLACEMENT (CC) | 545 |
| ENGINE TYPE | SOHC, 4-stroke, 4-valve |
| BORE & STROKE (MM) | 92x82 |
| COOLING SYSTEM | Liquid with fan |
| TRANSMISSION | Automatic CVT with EBS |
| DRIVE SYSTEM | 2/4 WD + Diff Lock |
| OVERALL WIDTH (IN./CM) | 47.5/120.6 |
| OVERALL HEIGHT (IN./CM) | 48/121.9 |
| OVERALL LENGTH (IN./CM) | 84.8/215.4 |
| WHEELBASE (IN./CM) | 50/127 |
| SUSPENSION TRAVEL FRONT (IN./CM) | 10/25.4 |
| SUSPENSION TRAVEL REAR (IN./CM) | 10/25.4 |
| GROUND CLEARANCE (IN./CM) | 11/27.9 |
| SUSPENSION TYPE - FRONT | Double A-Arm |
| SUSPENSION TYPE - REAR | Double A-Arm |

| | |
|--|--|
| FRONT BRAKES | Hydraulic Disc |
| REAR SERVICE BRAKE | Hydraulic Disc |
| TIRE FRONT (PRESSURE) | 25x8-12 (5) |
| TIRE REAR (PRESSURE) | 25x10-12 (5) |
| FUEL CAPACITY (GAL./LITERS) | 5.7/21.6 |
| RACK CAPACITY - FRONT (LBS./KG) | 100/45.4 |
| RACK/BOX STORAGE CAPACITY - REAR (LBS./KG) | 200/90.8 |
| TOWING CAPACITY (LBS./KG) | 1050/476.3 |
| ALTERNATOR CAPACITY (AMPS) | 25.0 |
| SPEEDOMETER | Analog |
| ODOMETER | Digital |
| DRY WEIGHT (LBS./KG) | 717/325.2 |
| MINIMUM OPERATOR AGE | 16 |
| AVAILABLE COLORS | Arctic Metallic Green Paint |
| SPECIAL FEATURES | Aluminum Wheels, Front & Rear Bumpers, Winch |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



450 H1 EFI

| | |
|----------------------------------|-------------------------|
| ENGINE DISPLACEMENT (CC) | 443 |
| ENGINE TYPE | SOHC, 4-stroke, 4-valve |
| BORE & STROKE (MM) | 89x71.2 |
| COOLING SYSTEM | Liquid with fan |
| TRANSMISSION | Automatic CVT with EBS |
| DRIVE SYSTEM | 2/4 WD + Diff Lock |
| OVERALL WIDTH (IN./CM) | 47.5/120.6 |
| OVERALL HEIGHT (IN./CM) | 48/121.9 |
| OVERALL LENGTH (IN./CM) | 84.8/215.4 |
| WHEELBASE (IN./CM) | 50/127 |
| SUSPENSION TRAVEL FRONT (IN./CM) | 10/25.4 |
| SUSPENSION TRAVEL REAR (IN./CM) | 10/25.4 |
| GROUND CLEARANCE (IN./CM) | 11/27.9 |
| SUSPENSION TYPE - FRONT | Double A-Arm |
| SUSPENSION TYPE - REAR | Double A-Arm |

| | |
|--|--------------------------|
| FRONT BRAKES | Hydraulic Disc |
| REAR SERVICE BRAKE | Hydraulic Disc |
| TIRE FRONT (PRESSURE) | 25x8-12 (5) |
| TIRE REAR (PRESSURE) | 25x11-12 (5) |
| FUEL CAPACITY (GAL./LITERS) | 5.7/21.6 |
| RACK CAPACITY - FRONT (LBS./KG) | 100/45.4 |
| RACK/BOX STORAGE CAPACITY - REAR (LBS./KG) | 200/90.8 |
| TOWING CAPACITY (LBS./KG) | 1050/476.3 |
| ALTERNATOR CAPACITY (AMPS) | 25.0 |
| SPEEDOMETER | Digital |
| ODOMETER | Digital |
| DRY WEIGHT (LBS./KG) | 685/310.8 |
| MINIMUM OPERATOR AGE | 16 |
| AVAILABLE COLORS | Red, Green or Lime Green |

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE